ISSN: 2582-4686 SJIF 2021-3.261,SJIF 2022-2.889,
2024-6.875 ResearchBib IF: 9.948 / 2024

THE MULTIDISCIPLINARY JOURNAL OF SCIENCE AND TECHNOLOGY

VOLUME-5, ISSUE-5

THE IMPACT OF THE BRAKE SYSTEM OF VEHICLES ON THE ENVIRONMENT AS A RESULT OF THE INGESTION OF PADS.

D.Sh.Chuyanov

Head of the department of transport doctor of technical sciense, professor (Karshi State Technical University) dchuyanov1@mail.ru

M.D.Buriyev

Department of vehicles doctor of technical philosophy, associate professor (Karshi State Technical University) muhriddin.boriyev@mail.ru

Abstract: Currently, information has been provided on the negative impact of particles generated during the braking process of cars on the environment, and the amount of particles released into the environment as a result of the wear of brake linings during the braking process of cars has been cited.

Base words: car, overhead, edible, road traffic accident, brake, gutters, atmosphere, hydrosphere, lithosphere, budget, crankcase, rotor, regulator, man-made.

The independence of the Republic of Uzbekistan, the rapid transition to the market economy, the development of private ownership, small and medium-sized businesses led to an increase in the material wealth of citizens and an increase in the number of not only personal light cars, but also, at the same time, private cargo cars and small-sized buses in Naija. The Republic of Uzbekistan has become one of the 28 countries in the world with its own automotive industry. Road Transport occupies an important place in the unified transport system of our country. It transports more than 80% of National Farm cargo, which is due to the high maneuverability of car transport, the ability to deliver cargo “door to door” on the road without additional loading, and therefore the high speed and safety of cargo delivery. Road Transport played a large role in the formation of the modern image of the population, the prevalence of intercity tourism, the territorial decentralization of the industrial and service sector. It is known that an increase in the level of motorization of the country, while strengthening its economic and defense capacity, can lead to many negative consequences. Such negative consequences are caused by an increase in the number of cars on highways, an increase in traffic flow density and road load levels, a deterioration in driver comfort for road traffic and, ultimately, an increase in the amount of traffic accidents, the number of people who are dying in them and receiving various body injuries, a decrease in traffic speed and many other. Today, the industrial activity of a person is associated with the use of various natural resources, covering many chemical elements. The increased man-made impact on the natural environment creates a number of environmental problems. The most acute are related to the state of the atmosphere, hydrosphere and lithosphere. The atmosphere plays an important role in all natural processes. It serves as reliable protection against harmful cosmic radiation and determines the climate of a particular area and the entire planet [1]. Atmospheric air is one of the main vital elements of the environment, its life-giving source. Protecting it, keeping it clean means saving life on Earth. Large cities, especially industrial production centers, are currently characterized by the strongest air pollution from automotive emissions, which is 40-50% of atmospheric pollution. Cars slow down with two types of brakes: drum brake system and disc brake system. Drum brake system-a large part of cars (mainly budget and middle-class models) are equipped with such mechanisms on the rear axle. They are very reliable and

ISSN: 2582-4686 SJIF 2021-3.261,SJIF 2022-2.889,
2024-6.875 ResearchBib IF: 9.948 / 2024

THE MULTIDISCIPLINARY JOURNAL OF SCIENCE AND TECHNOLOGY

VOLUME-5, ISSUE-5

stable. Due to the wear of the pads on such braking systems, a high gap is formed between the friction surface and the walls of the drums. The mechanism involves a regulator that covers this distance, bringing the pads as close to the drum walls as possible. The process of self-adjusting the mechanism occurs mainly during hard braking. The brakes are cooled by ribs and many metal parts located on the drum itself. Disc brake system-used on the front axle, sports cars and premium cars. The caliper clamps the brake disc on both sides. This arrangement requires little effort to slow down the wheel, so this system is more efficient than the drum's analogue. For this reason, the mechanisms load the temperature much higher. In modern discs, special grooves are made that improve heat dissipation. Such modifications are called ventilated [2].



Drum brake system



Disc brake system

Currently, Road Transport is the main source of atmospheric air pollution. The particles produced by the movement of cars are formed mainly from exhaust gas. The most important sources of solid harmful particles in the environment associated with the car are particles formed by braking from the ingestion of brake pads and tires[3]. The particles formed in the process of car braking are scattered around the environment. 50-70% of the particles formed during the braking process become the composition of atmospheric air. Initially larger particles than the wheel in the braking process (Less than 10 micrometers), followed by smaller air particles (less than 1 micrometer).

Raw material name	Density (kg/sm^3)	% Volume
Bonding silicon carbide	3,21	15
Filler barium ($BaSO_4$)	4,5	12
Synthetic graphite	2,32	8
Aliminum (Al_2O_3)	3,95	11
Zinc	7,14	9
Cox	1,506	8
Copper	5,7	19
Iron	7,874	18

Table-1. Chemical composition of breake pad material.

Particles of different sizes are causing negative harm to human health in a cloudy way. These particles are manifested in the form of dust in buildings located from highways. Heavy metals in particles have a negative impact on human health. The details of modern brake mechanisms are compositions consisting of various and sometimes unknown components. The chemical composition of the particles formed by the ingestion of the details of the brake mechanisms is significantly different from the chemical composition of the original coating material. In order to fully consider

ISSN: 2582-4686 SJIF 2021-3.261,SJIF 2022-2.889,
2024-6.875 ResearchBib IF: 9.948 / 2024

how the details of the brake mechanism affect the chemical composition of the particles formed by the ingestion, it is necessary to consider the composition of the materials used in its details and the particles formed by the ingestion. The chemical composition of the materials used in the production of brake pads is mainly composed of metals such as Fe, Cu, Zn and Pb. The percentage of Fe (iron) in the structure of the brake mechanism details can reach up to 60 percent, and this varies depending on the type of coating. Along with brake pads, brake discs also contribute to the environmental impact of the automotive industry. Most brake discs are made of cast iron, which makes it difficult to process the material effectively. However, disc brake primers rather than calodc brake primers recognize the importance of environmentally friendly practices, and it is necessary to invest in research and development to create recyclable brake discs. Using innovative materials and engineering technologies, it is necessary to minimize non-recyclable waste and reduce the overall impact on the environment.

As a result of friction between the brake pads and discs when we brake, microscopic particles are thrown into the air. These particles, known as brake dust, are made up of various materials such as metal, fibers and adhesive residues. Unfortunately, this waste can negatively affect both human health and the environment. Disc braking overhangs by developing low-dust brake pads and less particulate-forming disc surfaces, it is necessary to actively study ways to minimize brake dust. It helps to reduce waste as a result of premature replacement by producing high-quality and durable brake components. In addition, they train vehicle owners in proper brake maintenance methods that can further extend the life of brake pads and rotors. Regular inspection, cleaning and lubrication not only ensure optimal braking performance, but also provide a stable approach by minimizing unnecessary waste. At a time when the issue of environmental preservation is growing, it is necessary to develop not only highly efficient, but also environmentally friendly automotive parts. In conclusion, one car that travels an average of 15 thousand km per year consumes about 2 tons of fuel and about 26-30 tons of air, including 4.5 tons of oxygen (the latter is 50 times more than the annual consumption of a person). At the same time, the car releases carbon monoxide CO-700 kg, No. 2-40 kg, non-combustible hydrocarbons-230 kg, solids 2-5 kg into the atmosphere per year. In particular, lead emissions caused by the use of leaded gasoline can be identified [4]. Toxic emissions from the engine include exhaust and crankcase gases, fuel vapors from the carburetor and fuel tank. The main share of toxic impurities enters the atmosphere with exhaust gases. About 45% of the total hydrocarbon emissions enter the atmosphere with Carter gases and fuel vapors. Emissions into the environment occur primarily through the exhaust system of the car engine, and to a lesser extent through the ventilation system of the engine crankcase (crankcase gases), as well as hydrocarbon vapors of gasoline from the engine fuel system. The amount of hazardous waste to human health in the composition of car exhaust gases largely depends on the technical condition of the vehicles, in particular, on the condition of the engine. When the carburetor is not properly adjusted, the number of CO2 emissions increases by 4-5 times. The use of leaded gasoline leads to environmental pollution as lead enters the atmosphere, settles in soils and plants, and spreads through living organisms along the food chain. Thus, the average truck releases about 2.5-3 kg of lead per year. The atmosphere plays an important role in all natural processes. It serves as reliable protection against harmful cosmic radiation and determines the climate of a particular area and the entire planet. Atmospheric air is one of the main vital elements of the environment, its life-giving source. Protecting it, keeping it clean means saving life on Earth. In the near future: – the creation and expansion of production of cars with high-efficiency and low-toxic engines; the use of diesel engines and natural gas engines; - the creation

and introduction of effective systems for neutralizing exhaust gases; - the reduction of toxicity of motor fuels. Due to the pollution of the environment's internal combustion engines with harmful substances in the exhaust gases, entire regions, especially large cities, are becoming a zone of environmental destruction for the population. The problem of further reducing harmful emissions from engines is increasingly acute due to the constant increase in the fleet of working cars, the compression of traffic flows and the instability of measures to reduce harmful substances during Operation. The main directions of work in the field of protection of atmospheric air from pollution by vehicle emissions are: - the creation and expansion of production of vehicles with high – performance and low-toxic engines, including the further dieselization of vehicles; - the development of work on the creation and implementation of effective systems for neutralizing exhaust gases; - reducing the toxicity of motor fuels.

LITERATURE USED

1. http://www.lex.uz
2. K.Ismailov., A.Shermukhamedov., Z.Alimova., Determination of the Quantitiy of Particles Emmitted to the Environmet as a Result of Wearning car breake pads. Research square february 20 th, 2024-y.
3. International scientific journal science and innovation special issue: “transformation of education: the role of women in the development of science”, Avtomobillar tormoz ustquymalari yeyilishi natijasida atrof-muhitga chiqadigan zarralar miqdorini aniqlash Z.X.Alimova, K.G‘.Karimova, I.Sh.Berdiyorova february 16, 2024.
4. Theoretical justification of the parameters of the combined unit winding improvemen. Irgashev D.B., Bo‘riyev M.D., AMERICAN Journal of Engineering, Mechanics and Architecture Volume 2, Issue 2, 2024 ISSN (E): 2993-2637 157-162 paper.
5. Analysis of the coils Used in soil drilling. Irgashev D.B., Bo‘riyev M.D., American journal of engineering machenics and architect Volume 01 Issue 10, 2023 ISSN (E): 2993-2637. 302-308 paper.
6. Theoretical justification of the parameters of the combined unit winding improvemen. Bo‘riyev M.D., International Journal of Advanced Research in Science, Engineering and Technology ISSN: 2350-0328 Vol. 11, Issue 6, June 2024.
7. Qiya ustunli ishchi organning yuqori yumshatgich parametrlarini asoslash bo‘yicha tajribaviy tadqiqot natijalari. Irgashev D.B., Bo‘riyev M.D., Ganiyev B.G., O‘zbekiston Milliy axborot agentligi O‘zA Ilm-fan bo‘limi 2023-yil iyun soni №6 (44) 103-109 bet.
8. Justification of the bottom softening parameters of working organ with a sloping column. Mamatov F.M., Irgashev D.B., Bo‘riyev M.D. Ganiyev B.G., E3S Web of Conferences 434, 03010 (2023) ICECAE 2023.